

High Value

Superior Quality

Performance/Durability

Stylish Design

Heat/Cold Resistance



Windsor
Fully Assembled Patio Door



Features and Specifications



Sunview Patio Doors' value-priced series starts with the most advanced vinyl. A high-grade resin unmatched for strength and freedom from wear – it will not rot, rust, pit or blister over long periods of time. **Door ships assembled.**



Elegant Hardware

Available in standard white and black, with an optional upgrade to satin nickel.



Optional Locks

Two-Position Kick Locks mount on the bottom of the operating door. Used as secondary lock when the door is closed and available in white, beige, or brown.

Twin-point Locks provide **two** heavy-duty locking points on the door frame. Available on all hardware handles.

Glazing

High-performance glazing with **Low-E** glass and **Super Spacer®** technology.

Super Spacer®



Optional Decorative Grills

Internal grills are available in a wide range of design styles with colours that include **Flat Grills** in two-tone, white, brass and pewter, **Georgian Grills** in white, and **Pencil Grills** in white, brass and pewter.




Frame

- Double perimeter seals
- 4^{7/8}" welded vinyl frame
- Components easily installed and replaceable
- Stainless steel roller track


Welded Sash

- Reinforced with steel to withstand higher wind loads
- Double perimeter seal for superior air-tightness
- Doors are easily and completely reversible
- Adjustable nylon tandem ball-bearing rollers
- 1" sealed units for optimal thermal performance

Dimensions Door/Panel Configurations and Finished Sizes




OX-Slide left




XO-Slide Right

2 Panels

59¹/₂ W x 79¹/₂ H
71¹/₂ W x 79¹/₂ H
95¹/₂ W x 79¹/₂ H



OXO-Slide R to L or
OZO-Slide L to R



OOX-Slide R or OOX Slide L

3 Panels

87¹/₂ W x 79¹/₂ H
105¹/₂ W x 79¹/₂ H
141¹/₂ W x 79¹/₂ H

Optional Exterior Colours

Sunview's patio doors boast a wide range of exterior colour options that feature a durable finish that is also UV stable.



Performance

Standard	Configuration	Performance Class and Grade	Air Leakage	Water Penetration Resistance	Design Pressure
AAMA/WDMA/CSA 101/1.S.2/A440-11 and CSA A440S1-09	OX / XO	R-PG40	A3-0.3 L/s-m ²	360 Pa (7.5 psf)	±1920 Pa (±40 psf)



Intertek



NFRC
National Fenestration Rating Council®

Distributed By:



Our products meet the Energy Star program guidelines for helping businesses and individuals protect the environment through superior energy efficiency.



www.sunviewdoors.com